

MOOVMOR

SP14 SKIPPAKER

PORTABLE COMPACTOR



+353 45 521031



sales@moovmor.com



www.moovmor.com

MOOV MOR

SP14 SKIPPAKER

PORTABLE COMPACTOR

OVERVIEW

The Moovmor SP14 Skippaker is our all-in-one skip type portable compactor which is a popular choice for hotels, hospitals and other food and catering operations. The SP14 is a sealed unit and can be supplied normally for either hand loading or with an end loading wheelie bin tipper. For the bin tipping option it is normal to have a mobile safety cage complete with interlocked access to the lifter and comb lift allows for tipping either two or four wheeled containers.



STANDARD FEATURES

- All-in-One compactor and container unit
- Low-level hand loading height for ease of access
- Pre full and bin full warning signals
- Pull out power pack for easy servicing access
- Rear door sealing to retain liquid residue
- Curved rear door for maximum strength
- Built to CHEM specification
- Designed and manufactured to EU machinery directives and certified CE compliant

BENEFITS

- Designed with maximum operator safety in mind
- Minimum space required – average car parking space
- All-in-one unit means no waste escape when emptying
- Low running costs with Moovmor low energy power pack systems
- Low energy carbon footprint
- Easy to operate and load
- Ideal compactor to replace multiple wheelie bins
- Reduced manual handling and risk to staff
- Streamlined operations
- Maximum payload on each lift
- Maximum performance and life long reliability

OPTIONAL FITOUTS



Open top hopper for bulk loading




Bin lift activated bonnet style hopper lid



GSM modules with performance monitoring & notification system



Enclosed hopper with interlocked access door



Single phase option



Off dock loading



Comb type bin tipper for 120 to 1100 litre wheeled carts



Reverse pick up facility for off dock loading



Guide rail and in-floor plates

SP14 SKIPPAKER PORTABLE COMPACTOR

SPECIFICATION	SP14 SKIPPAKER
COMPACTION FORCE @ 200 BAR (TONNES)	22
MOTOR POWER (KW)	4 kW, 16A
POWER SUPPLY	3 PH + E + N, 400V, 50Hz or Single Phase 230v
STD FACTORY SET CYCLE TIME (SECS)	37
CHARGE BOX VOLUME (M ³)	0.78
CHEM VOLUME PER STROKE (M ³)	0.65
CYLINDER BORE (MM)	80 x 2
COMPACTOR LENGTH (MM)	4230
COMPACTOR WIDTH (MM)	1905
COMPACTOR HEIGHT (MM)	2180
CHARGE BOX LOADING HEIGHT (MM)	950/1190
CHAMBER WIDTH (MM)	1500
CHAMBER LENGTH (MM)	740
CHAMBER HEIGHT (MM)	950
COMPACTOR WEIGHT (KG)	3500

Due to company policy of continued product development design and specifications are subject to change without notice. Check with your local distributor or our customer service representative for regional availability within Europe.